

# HT4

0.3-0.6 mm thick

Excellent protective coating that enhances the chemical resistance of Stonclad flooring systems.

Easily applied and hardens to an attractive gloss finish.

## FEATURES:

- Attractive appearance
- Long-term abrasion and corrosion resistance
- Excellent bond strength
- Protects against moisture penetration
- Durable gloss finish
- Outstanding cleanability

# 731

A protective industrial sealer for wood, masonry and concrete. Ideal for “back of house” retail outlet floors.

731 is a UV stable heavy duty polyurethane roll on application that is used in retail, back of house, workshops etc.

## FEATURES:

- Clear or pigmented
- Excellent colour stability
- Glossy, tile-like topcoat
- High gloss durable finish
- Resists mild chemicals
- Thin film

## TECHNICAL PROFILE COMPONENTS

Two component, 100% solids epoxy coating.

### COLOUR

Refer to Stonkote colour chart

### CURE RATE AT 25” C

4-5 Hours for tack-free surface and 24 hours for normal operation

### HEAT RESISTANCE LIMITATION

Continuous: 93°C

Intermittent: 121°C

### OTHER

|                |                    |
|----------------|--------------------|
| Percent solids | 100%               |
| Flame spread   | Self-extinguishing |

## COMPONENTS

Two component, clear or coloured, solvent-based polyurethane. Apply primer + 2 topcoats.

### COLOUR.

Light Grey, Grey, Dark Grey, Brilliant Green, Golden Yellow, Signal Red, White and Clear.

### CURE RATE

4-6 Hours tack-free, 12 hours overcoat and 48 hours for service. Application temperature range of 10°C to 30°C. Cannot be applied in direct sunlight.

### OTHER

|                |                                    |
|----------------|------------------------------------|
| Percent solids | Clear 40%<br>Colours 46%           |
| VOC Content    | Clear: 572 g/l<br>Colours: 500 g/l |

\*Typical properties at 25”C  
For a full Technical profile, please contact [info@nuvo.co.za](mailto:info@nuvo.co.za).